



IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)

BBCV2.MH59963

Lithium Batteries - Component

If you notice a change to your BBCV2 Listing Card, click [here](#) to learn more.

[Page Bottom](#)

Lithium Batteries - Component

[See General Information for Lithium Batteries - Component](#)

MASTER BATTERY, S.L.

MH59963

2 Dehesa Vieja Street
La Dehesa Industrial Park
Madrid 28052
SPAIN

Model No.	Secondary Type ^[d]	Max Charging Current (Ic), mA	Max Charging Voltage, V dc ^[e]	Test Compliance ^[f]
103627	Lithium ion (Prismatic)	1160	4.35	1
132832	Lithium ion (Prismatic)	1100	4.2	1
14400 600mAh	Lithium ion (Cylindrical)	600	4.6	1
14430 650mAh	Lithium ion (Cylindrical)	650	4.6	1
14430 700mAh	Lithium ion (Cylindrical)	700	4.6	1
14430-400	Lithium ion (Cylindrical)	400	3.65	1
14430-450	Lithium ion (cylindrical)	450	3.65	1
14500	Lithium ion (Cylindrical)	750	4.6	1
14500 800mAh	Lithium ion (Cylindrical)	800	4.6	1
14500-500	Lithium ion (cylindrical)	500	3.65	1
14500-550	Lithium ion (cylindrical)	550	3.65	1
14500/600	Lithium ion (Cylindrical)	600	3.65	1
15260/250	Lithium ion (Cylindrical)	250	3.65	1
16340/500	Lithium ion (Cylindrical)	500	3.65	1
17360 700mAh	Lithium ion (Cylindrical)	700	4.6	1
17360 750mAh	Lithium ion (Cylindrical)	750	4.6	1
17360 800mAh	Lithium ion (Cylindrical)	800	4.6	1
18490 1100mAh	Lithium ion (Cylindrical)	1100	4.6	1
18490 1250mAh	Lithium ion (Cylindrical)	1250	4.6	1
18490 1400mAh	Lithium ion (Cylindrical)	700	4.6	1
18490 1600mAh	Lithium ion (Cylindrical)	800	4.6	1
18490-1000	Lithium ion (cylindrical)	1000	3.65	1
18490-800	Lithium ion (cylindrical)	800	3.65	1
18650 2000mAh	Lithium ion (Cylindrical)	1000	4.6	1

18650 2200mAh	Lithium ion (Cylindrical)	1100	4.6	1
18650 2600mAh	Lithium ion (Cylindrical)	1300	4.6	1
18650-1100	Lithium ion (cylindrical)	1100	3.65	1
18650-1300	Lithium ion (cylindrical)	1300	3.65	1
18650-1400	Lithium ion (cylindrical)	1400	3.65	1
18650-1500	Lithium ion (cylindrical)	1500	3.65	1
18650/1600	Lithium ion (Cylindrical)	1600	3.65	1
22430 1600mAh	Lithium ion (Cylindrical)	800	4.6	1
22650-2000	Lithium ion (Cylindrical)	2000	3.65	1
26500/2400	Lithium ion (Cylindrical)	2400	3.65	1
26650-3000	Lithium ion (cylindrical)	3000	3.65	1
26650-3300	Lithium ion (cylindrical)	3300	3.65	1
26650/3400	Lithium ion (Cylindrical)	3400	3.65	1
26650/3500	Lithium ion (Cylindrical)	3500	3.65	1
26650/3600	Lithium ion (Cylindrical)	3600	3.65	1
26650/3800	Lithium ion (Cylindrical)	3800	3.65	1
26650/4000	Lithium ion (Cylindrical)	4000	3.65	1
32650-5000	Lithium ion (cylindrical)	5000	3.65	1
32650-5500	Lithium ion (cylindrical)	5500	3.65	1
32700/6000	Lithium ion (Cylindrical)	6000	3.65	1
32700/6250	Lithium ion (Cylindrical)	6250	3.65	1
32700/6500	Lithium ion (Cylindrical)	6500	3.65	1
32700/6750	Lithium ion (Cylindrical)	6750	3.65	1
32700/7000	Lithium ion (Cylindrical)	7000	3.65	1
395057	Lithium ion (Prismatic)	1250	4.2	1
483436	Lithium ion (Prismatic)	600	4.2	1
484655	Lithium ion (Prismatic)	1500	4.2	1
495060	Lithium ion (Prismatic)	2000	4.35	1
503450	Lithium ion (Prismatic)	900	4.2	1
504281	Lithium ion (Prismatic)	2000	4.4	2
515477	Lithium ion (Prismatic)	2000	4.35	1
533443	Lithium ion (Prismatic)	850	4.2	1
543136	Lithium ion (Prismatic)	650	4.2	1
563436	Lithium ion (Prismatic)	650	4.2	1
565571	Lithium ion (Prismatic)	2000	4.35	1
603443	Lithium ion (Prismatic)	950	4.2	1
982734	Lithium ion (Prismatic)	1000	4.35	1

[d] These cells and batteries are rechargeable. The circuitry containing these cells or batteries is to contain protective components intended to protect the cells or batteries from currents in excess of the maximum charging current and voltage indicated.

[e] The Max Charging Voltage noted in the column is the maximum voltage employed during the abnormal charging test of the secondary lithium ion cell. However, the maximum recommended charging voltage for lithium ion cells is 4.2 V, unless indicated otherwise.

[f] Test Compliance - The cells comply with the tests in UL 1642 as noted:

- 1 - Complies with all single-cell tests
- 2 - Complies with all single-cell tests except the impact test

3 - Complies with all single-cell tests except the projectile test

4 - Complies with all single-cell tests except the crush test

Marking: Company name, Recognized Component Mark,  on the cell or smallest shipping package containing the cell.
Last Updated on 2018-11-15

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".